



## Safety Data Sheet Killgerm ULV 1500 (Insecticide)

9	Physical and chemical properties	Appearance: pH: Flash point: Flammability: Bulk density: Solubility: Odour: Incompatibility:	Straw coloured liquid. Not applicable. 67°C. Flammable, will burn at room temperatures to evolve toxic combustion products. 0.834 Insoluble in water. Slight kerosene odour. Incompatible with strong oxidising agents, strong acids and strong bases.
10	Stability and reactivity	Product is stable and not a reactive substance.	
11	Toxicological information	Routes of entry/symptoms of contact:	
		Inhalation:	In normal circumstances, the low volatility of this product does not give rise to harmful concentrations. Precautions should be taken to prevent exposure to product spray/mist.
		Skin and eyes:	Odourless kerosene is a moderate skin irritant. Prolonged or repeated contact can give rise to severe irritation or cause dermatitis. Irritating to eyes.
		Ingestion:	The main hazard of swallowing the product arises from any consequent aspiration into the lungs which may cause chemical pneumonitis.
12	Ecological information	DANGEROUS TO FISH AND AQUATIC LIFE. Do not contaminate watercourse or ground.	
13	Disposal considerations	Empty containers: Unused/recovered materials: Contaminated PPE:	Do not re-use – empty completely. Dispose of as below. Do not dispose in domestic waste. Treat as controlled waste. Do not dispose in domestic waste. Treat as controlled waste.
14	Transport information	Not classified as hazardous for transport.	
15	Regulatory information	Approved under COPR. HSE no. 6961 (IP.IFSP.AH) Refer to other relevant measures such as Health & Safety at Work etc. Act and the COSHH regulations. The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by legislation	
16	Other information	Use only in accordance with label instructions. Observe statutory conditions of use on the label. Always read the label. Use pesticides safely. Odourless kerosene has been assigned an OEL of 300ppm by the manufacturer.	